

### DESCRIPTION

The GBLCxxl Series are ultra low capacitance transient voltage suppressor arrays, designed to protect applications such as portable electronics and SMART phones. This series is available in unidirectional configurations and is rated at 350 Watts for an 8/20 $\mu$ s waveshape.

The GBLCxxl and Series meets IEC 61000-4-2 (ESD) and IEC 61000-4-4 (EFT) requirements. At higher operating frequencies or faster edge rates, insertion loss and signal integrity are a major concern. This series offers an ultra low capacitance and low leakage current in a miniature SOD-323 package.

### FEATURES

- ✧ IEC61000-4-2 (ESD)  $\pm 15\text{kV}$  (air),  $\pm 8\text{kV}$  (contact)
- ✧ IEC61000-4-4 (EFT) 40A (5/50 $\mu$ s)
- ✧ IEC61000-4-5 (Lightning)
- ✧ Protects one I/O line (bidirectional)
- ✧ Low clamping voltage
- ✧ Working voltages : 3V, 5V, 8V, 12V, 15V, 24V
- ✧ Low leakage current
- ✧ Response Time is < 1 ns

### MACHANICAL DATA

- ✧ SOD-323 package
- ✧ Flammability Rating: UL 94V-0
- ✧ Packaging: Tape and Reel
- ✧ High temperature soldering guaranteed: 260 $^{\circ}\text{C}$  /10s
- ✧ Reel size: 7 inch
- ✧ MSL1


### ORDERING INFORMATION

- ✧ Device: GBLCxxl
- ✧ Package: SOD-323
- ✧ Material: Halogen free
- ✧ Packing: Tape & Reel
- ✧ Quantity per reel: 3,000pcs

### APPLICATIONS

- ✧ Cell Phone Handsets and Accessories
- ✧ Microprocessor based equipment
- ✧ Personal Digital Assistants (PDA's)
- ✧ Notebooks, Desktops, and Servers
- ✧ Portable Instrumentation
- ✧ Peripherals
- ✧ USB Interface

### PIN CONFIGURATION



### PACKAGE OUTLINE




## ABSOLUTE MAXIMUM RATING

| Symbol    | Parameter                                                      | Value               | Units |
|-----------|----------------------------------------------------------------|---------------------|-------|
| $V_{ESD}$ | ESD per IEC 61000-4-2 (Air)<br>ESD per IEC 61000-4-2 (Contact) | $\pm 15$<br>$\pm 8$ | kV    |
| $P_{PP}$  | Peak Pulse Power (8/20 $\mu$ s)                                | 350                 | W     |
| $T_{OPT}$ | Operating Temperature                                          | -55/+150            | °C    |
| $T_{STG}$ | Storage Temperature                                            | -55/+150            | °C    |
| $T_L$     | Lead Soldering Temperature                                     | 260                 | °C    |


## ELECTRICAL CHARACTERISTICS (Tamb=25°C)

| PART<br>NUMBER | DEVICE<br>MARKING | $V_{RWM}$<br>(V) | $V_B@1mA$<br>(V) | $V_C@1A$<br>(V) | $V_C@I_{pp}$<br>(V) |                 | $V_C@I_{pp}$<br>(V) |                 | $I_R$<br>( $\mu A$ ) | $C_T$<br>(pF) |
|----------------|-------------------|------------------|------------------|-----------------|---------------------|-----------------|---------------------|-----------------|----------------------|---------------|
|                |                   | Max              | Min              | Max             | Max                 | $I_{pp}$<br>(A) | Max                 | $I_{pp}$<br>(A) | Max                  | Typ.          |
| GBLC03I        | C                 | 3.0              | 4.0              | 7.0             | 13.9                | 8               | 20.0                | 20              | 5                    | 0.8           |
| GBLC05I        | A                 | 5.0              | 6.0              | 9.8             | 18.3                | 8               | 20.0                | 18              | 1                    | 0.8           |
| GBLC08I        | B                 | 8.0              | 8.5              | 13.4            | 18.5                | 8               | 24.0                | 18              | 1                    | 0.8           |
| GBLC12I        | D                 | 12.0             | 13.3             | 19.0            | 24.0                | 6               | 28.6                | 12              | 1                    | 0.8           |
| GBLC15I        | E                 | 15.0             | 16.7             | 24.0            | 29.0                | 5               | 31.8                | 10              | 1                    | 0.8           |
| GBLC24I        | H                 | 24.0             | 26.7             | 43.0            | 45.0                | 3               | 56.0                | 6               | 1                    | 0.8           |


### ELECTRICAL CHARACTERISTICS CURVE




**Pulse Waveform**



**Non-Repetitive Peak Pulse Power vs. Pulse Time**




**Power Derating Curve**




**Junction Capacitance vs. Reverse Voltage**

## SOD-323 PACKAGE OUTLINE DIMENSIONS



| Symbol | Dimensions In Millimeters |       |
|--------|---------------------------|-------|
|        | Min                       | Max   |
| A      |                           | 1.00  |
| A1     | 0.000                     | 0.100 |
| A2     | 0.800                     | 0.900 |
| b      | 0.250                     | 0.350 |
| c      | 0.080                     | 0.150 |
| D      | 1.200                     | 1.400 |
| E      | 1.600                     | 1.800 |
| E1     | 2.500                     | 2.700 |
| e      | 1.800                     | 2.040 |
| L      | 0.475 REF                 |       |
| L1     | 0.250                     | 0.400 |
| θ      | 0°                        | 8°    |



**Recommended Pad outline**